

The LED emergency exit light box comes complete with a green up legend depicting a running man and a up arrow. Features an easy access, quick test button underneath the fitting, saving time and resources. A green LED indicator light makes it quick and easy to visually confirm that the battery is successfully and continuously receiving a charge

- Sticker Legend Kit with Up, Down, Left, Right arrows, blanks and running man
- 6500K, Daylight White
- 3+ hours emergency function
- Maintained or non-maintained dual function
- Self-Test option available













Technical Specification

Product Details	
Range Variants	Standard / Self-Test
Applications	Commercial or Semi-Commercial
Installation Options	Ceilings / Walls / Public Rooms / Doorways / Emergency Escape Routes
UKCA & CE Compliant	Yes
RoHS Compliant	Yes
Guarantee Period	3 years (fitting), 2 years (battery)

Construction	struction		
Case Material	Polycarbonate		
Case Colour	White		
Diffuser Material	Polycarbonate		
Diffuser Colour	Clear		
IP Rating	IP65		
Dimensions	70mm (h) x 360mm (w) x 110mm (d)		
Weight	0.470 kg		
Operating Temp (°C)	-20 to 45 °C		
Viewing	24M		

Distance

Electrical Data	
Voltage	220-240V AC
Frequency	50/60Hz
Wattage (illuminated)	4.5W
Battery Type	LiFePO4 battery
Battery voltage	3.2V 1000mAh
Emergency	Maintained & Non-Maintained
Emergency Wattage	3.0W
Battery Life	>3 hours
Earth Protection	Class II
Driver	Integrated
Dimmable	No


LED Data				
LED Type	SMD			
LED Microchip	2835			
Lumens	220 lm			
Lumens per watt	49.0 lm/W			
Lms in Emergency mode	130 lm			
Colour Rendering Index	>=80 CRI			
Colour Temperature	6500K (Daylight White)			
Instantaneous Illumination	Yes: <1 second			
LED Lifetime	50,000 hrs			


Product Family

sku	type	finish
ВНЕМ5	IP65 Emergency Bulkhead	White
BHEM5-ST	IP65 Emergency Self-Test Bulkhead	White



Fixing Detail







Additional Images













