

## AXIO.

The LightHub Emergency LED downlight assists in the compliance of regulations BS 5266 and BS EN 1838:2013 for emergency lighting in commercial, public and accommodation premises.

- √ 6500K, Daylight White
- Operates at 150 lumens on battery for 3hrs
- Complete with 3 bezels White, silver and black
- √ 3hr Emergency Non-maintained
- ✓ Slim profile only 26mm depth











## **Technical Specification**

<b>Product Details</b>				
Range Variants	Emergency			
Trim Options	White / Silver / Black			
Applications	Commercial or Semi- Commercial			
Installation Options	Corridors / Hotels & B&Bs / Offices / Receptions / Retail / Restaurants / Shops / Stairwells			
UKCA & CE Compliant	Yes			
RoHS Compliant	Yes			
Guarantee Period	2 years (fitting), 2 years (battery)			

Construction	
Case Material	Polycarbonate
Case Colour	White
Trim Colour Options	White / Silver / Black
IP Rating	IP20
Dimensions	Diameter: 60mm x Depth: 26mm
Weight	0.2 kg
Operating Temp (°C)	-20 to 40 °C
Cable Entry	Driver

Electrical Data							
Voltage	220-240V AC						
Frequency	50/60Hz						
Wattage (illuminated)	2.0W						
Battery Type	LiFePO4						
Battery voltage	3.2V 1500mAh						
Emergency Wattage	2.0W						
Battery Life	>3 hours						
Power Factor							
Earth Protection	Class I						
Driver	Integrated						
Dimmable	No						

LED Data			
LED Type	SMD		
LED Microchip	2835		
Lumens per watt	75 lm/W		
Lms in Emergency mode	150 lm		
Colour Rendering Index	>=80 CRI		
Colour Temperature	6500K (Daylight White)		
Beam Angle	120°		
Instantaneous Illumination	Yes: <1 second		
LED Lifetime	25,000 hrs		

## **Product Family**

SKU	гуре		IIIIISII					
DLEM2	Emergency Mini	Downlight	White	_				
<b>→</b> 48mm								
						42 mm		
960nm				22	20mm			•
Ī	$\bigcirc$			010			Op.	
		I		212mm	<b></b>	27 mm		

