

# ELDON.

Plaster-in adjustable gu10 downlights are designed to be plastered into a ceiling during the early stages of a build allowing for the downlight to be fitted at a later stage and to conceal the bezel which gives a seamless and trimless finish.

- ✓ Quick fit push terminal block
- ✓ GU10 bulb required
- Designed for seamless finish
- ✓ Fully adjustable 20 degree tilt





#### **Technical Specification**

Product Details		Construction	
Range Variants	Standard	Case Material	Al
Trim Options	Round or Square	Case Colour	W
Applications	Commercial or Residential	Trim Colour Options	W
Installation Options	Ceilings	IP Rating	IP
UKCA & CE Compliant	Yes	_	12 55
RoHS Compliant	Yes	 Dimensions	C
Guarantee Period	2 year	_	12 12 55
			Ro

Construction	
Case Material	Aluminium
Case Colour	White
Trim Colour Options	White
IP Rating	IP20
Dimensions	Round: 120mm (dia) x 55mm (d) Square: 122mm (w) x 122mm (l) x
	55mm (d)
Cut-Out	Round: 82mm Square: 85 x 85mm
Cable Entry	Driver
Operating Temp	-20 to 45 °C

Electrical Data	
Voltage	220-240V AC
Frequency	50/60Hz
Wattage	50W
Power Factor	0.9 pf
Earth Protection	Class II
Dimmable	Yes with compatible dimmers and lamps

	Lamp Data	
С	Lampholder	GU10
	Tilt Angle	20°
mnotible		



GU10 LED (Sold Seperately)

## **GU10** Options

sku	description	dimmable
LA6GUWW	6W, 3000K Warm White	Yes
LA6GUCW	6W, 4000K Neutral White	Yes
LA6GUDL	6W, 6500K Daylight White	Yes

## **Product Family**

sku	finish
DLTMR	Round
DLTRSQ	Square





#### **Dimensions**





