

# SL-ACF

## LED BATTEN 110V ANTI CORROSIVE

## SITE LIGHTING



| Code            | Desc.                                           | Wattage | Lumen  | Length |
|-----------------|-------------------------------------------------|---------|--------|--------|
| SL-ACF-2        | 2Ft. Anti Corrosive                             | 20W     | 2600LM | 640mm  |
| SL-ACF-2-1MJBOX | Anti Corrosive + 1M Yellow cable + Junction box | 20W     | 2600LM | 640mm  |
| SL-ACF-4        | 4Ft. Anti Corrosive                             | 25W     | 3250LM | 1230mm |
| SL-ACF-4-1MJBOX | Anti Corrosive + 1M Yellow cable + Junction box | 25W     | 3250LM | 1230mm |
| SL-ACF-5        | 5Ft. Anti Corrosive                             | 35W     | 4550LM | 1530mm |
| SL-ACF-5-1MJBOX | Anti Corrosive + 1M Yellow cable + Junction box | 35W     | 4550LM | 1530mm |

### PRODUCT DETAILS

|              |               |
|--------------|---------------|
| Product code | See table     |
| Finish       | Yellow        |
| RAL colour   | -             |
| Material     | Polycarbonate |
| Diffuser     | Opal          |
| Width        | 85mm          |
| Height       | 80mm          |
| Length       | See table     |
| Warranty     | 3 Year        |

### OUTPUT

|                |                |
|----------------|----------------|
| LED type       | Integrated LED |
| Lumen output   | See table      |
| Lumen per Watt | 130Lm/W +/-    |
| Beam angle     | 120°           |
| Colour temp    | 4000K          |

### TECHNICAL DATA

|                 |           |
|-----------------|-----------|
| Volt            | 100-120V  |
| Watt            | See table |
| Class           | I         |
| Dimmable        | No        |
| Wiring          | Parallel  |
| Connector       | Pushfit   |
| CRI             | >80       |
| IP Rating       | 65        |
| IK Rating       | 08        |
| Operating temp. | 0° / +30° |

### OTHER INFORMATION